



Product of India

REMANUFACTURED SOLID TYRES



	BUDGET	GH0	GC0
		3-STAGE REMANUFACTURED STEEL BEAD-TO-BEAD	3-STAGE REMANUFACTURED STEEL PRECURED
	Ride	Normal, Low Rolling Resistance	Normal, Low Rolling Resistance
	Operating Conditions	Normal, continuous use	Normal, continuous use
1	No beads		
2	Hoop rings	GH02X	GC02X
3	Creel beads		
4	Clip		

TYRE SPECIFICATIONS								
TYRE SIZE	TYRE SIZE (METRIC)	RIM	TREAD	Tyre dimensions in mm			Tyre load capacity on fork lifts, kg at 25kmph	
				Outer Dia.	Sidewall width	Tread width	Load wheel	Steer wheel
3.00 - 4		2.10	LUG	245	85	75	260	195
3.50 - 4		2.10	LUG	250	89	83	260	195
4.00 - 4		2.50	LUG	300	92	84	535	412
3.50 - 5		3.00	LUG	300	100	90	900	690
4.00 - 8		2.75	LUG	402	103	86	950	730
4.00 - 8		3.00	LUG	402	103	86	950	730
4.00 - 8		3.75	LUG	405	119	86	950	730
12x3 1/2 - 8		3.00	LUG	308	98	87	850	650
	100/80-8	2.50	LUG	360	105	90	1,000	770
15X4 1/2 - 8	125/75-8	3.00	LUG	368	105	90	1,040	800
15X4 1/2 - 8	125/75-8	3.00	LUG	378	110	100	1,040	800
500 - 8		3.00	LUG	450	120	110	1,415	1,090
5.00 - 8		3.75	LUG	450	125	110	1,415	1,090
16X6 - 8	150/75-8	4.33	LUG	406	140	125	1,270	975
17X7 - 8		4.33	LUG	430	150	134	2,000	1,540
18X7 - 8	180/70-8	4.33	LUG	450	157	142	2,145	1,650
	140/55 - 9	4.00	LUG	376	125	110	1,170	900
6.00 - 9		4.00	LUG	520	138	120	1,885	1,450
21X8 - 9	200/75-9	6.00	LUG	517	188	157	2,755	2,120
	200/50 - 10	6.50	LUG	454	190	160	2,470	1,900
6.50 - 10		5.00	LUG	566	160	140	2,340	1,800
6.50 - 10		5.50	LUG	566	160	140	2,340	1,800
7.50 - 10		5.00	LUG	630	170	150	3,070	2,360
7.50 - 10		5.50	LUG	630	170	150	3,070	2,360
23X9 - 10	225/75-10	6.50	LUG	580	194	178	3,160	2,430
7.00 - 12		5.00	LUG	646	172	150	2,920	2,240
23X10 - 12		8.00	LUG	580	232	200	3,770	2,900
27X10 - 12	250/75-12	8.00	LUG	672	240	200	3,900	3,000
23X5 - 13		3.75	LUG	605	122	102	1,495	1,150
7.00 - 15		5.50	LUG	705	180	158	3,545	2,725
7.50 - 15		5.50	LUG	736	193	168	3,900	3,000
7.50 - 15		6.00	LUG	736	193	168	3,900	3,000
7.50 - 15		6.50	LUG	736	193	168	3,900	3,000
8.15-15 (28X9-15)	225/75-15	7.00	LUG	678	221	190	3,445	2,650
8.25 - 15		6.50	LUG	808	192	173	4,750	3,650
2.50 - 15	250/70-15	7.00	LUG	706	220	190	4,745	3,650
2.50 - 15	250/70-15	7.50	LUG	706	220	190	4,745	3,650
3.00 - 15	315/70-15	8.00	LUG	806	242	223	5,850	4,500
28X12.5-15	345/45-15	9.75	LUG	705	275	255	5,525	4,250
	355/65-15	9.75	LUG	810	285	265	7,000	5,450
	400/60-15	11.00	LUG	810	318	298	8,970	6,900
7.50 - 16		5.50	LUG	736	193	168	3,900	3,000
7.50 - 16		6.00	LUG	736	193	168	3,900	3,000
7.50 - 16		6.50	LUG	736	193	168	3,900	3,000
8.25 - 16		5.50	LUG	808	192	173	4,750	3,650
8.25 - 16		6.00	LUG	808	192	173	4,750	3,650

7.50 - 20		6.00	LUG	870	200	175	3,900	3,250
8.25 - 20		6.50	LUG	915	200	180	4,380	3,650
	355/50 - 20	10.00	LUG	810	285	265	8,970	6,900
9.00 - 20		6.50	LUG	972	226	191	5,400	4,500
9.00 - 20		7.00	LUG	972	226	191	5,400	4,500
10.00 - 20		7.00	LUG	1,004	250	203	6,000	5,000
10.00 - 20		7.50	LUG	1,004	250	203	6,000	5,000
10.00 - 20		7.50	LUG	1,050	265	235	6,000	5,000
10.00 - 20		8.00	LUG	1,004	250	203	6,000	5,000
10.00 - 20		8.00	LUG	1,050	265	235	6,000	5,000
10.00 - 20		8.50	LUG	1,004	250	203	6,000	5,000
10.00 - 20		8.50	LUG	1,050	265	235	6,000	5,000
11.00 - 20		7.50	LUG	1,050	265	235	6,000	5,000
11.00 - 20		8.00	LUG	1,050	265	235	6,000	5,000
11.00 - 20		8.50	LUG	1,050	265	235	6,000	5,000
12.00 - 20		8.00	LUG	1,080	255	232	7,560	6,300
12.00 - 20		8.00	LUG	1,140	295	250	7,560	6,300
12.00 - 20		8.50	LUG	1,080	255	232	7,560	6,300
12.00 - 20		8.50	LUG	1,140	295	250	7,560	6,300
13.00 - 20		8.00	LUG	1,140	295	250	7,560	6,300
13.00 - 20		8.50	LUG	1,140	295	250	7,560	6,300
12.00 - 24		8.50	LUG	1,165	265	230	8,040	6,700
12.00 - 24		10.00	LUG	1,165	285	245	8,280	6,900
14.00 - 24		10.00	LUG	1,275	308	270	11,100	9,250
14.00 - 25		10.00	LUG	1,275	308	270	11,100	9,250

All dimensions are nominal and depend on the condition and design of the original tyre. We reserve the right to offer Avatar tyres with variations in overall dimensions

NOTE: All Avatar tyres are remanufactured from used solid tyres and availability is limited

SPECIAL NOTES

- Availability is limited
- The Avatar GH0 is remanufactured from bead to bead, so the finish of the tyre is almost like brand new.
- The Avatar GC0 is remanufactured with a pre-cured tread, with the sidewall cosmetically improved.
- Service life depends on severity of operating conditions

Website: www.sun-tws.com

Contact: crm@sun-tws, info@sun-tws.com

Corporate Office:

SUN TYRE & WHEEL SYSTEMS

180 Mount Road, Chennai 600006, India

Phone #: +91-44-28525289

Manufacturing locations:

Plant #1 at A1-F3/A, New Sidco Industrial Estate
Maraimalainagar 603209, India

Plant #2 at Lot 2, Block B, Biyagama Export Processing Zone
Colombo, Sri Lanka

Plant # 3 *Under Construction* @
7/B1, Sipcot Industrial Complex, Pudukottai,
Tamil Nadu, India