



Product of India

# INDUSTRIAL PNEUMATIC TYRES



**TANTOR**

<b>TANTOR</b>	
Grade	<b>STANDARD</b>

TYRE SPECIFICATIONS								
Size	P.R.	Rim	Overall	Section	Tread	Load capacity on forklifts, 25kmph		Inflation Pressure (Bar)+/- 15%
			Dia.	Width	Depth	Load Wheel	Steer Wheel	
			(mm)	(mm)	(mm)	(kg)	(kg)	
5.00-8	10	3.50D	468	144	12	1415	1090	10
18x7-8	16	4.33R	465	173	14	2145	1650	10
6.00-9	10	4.00E	540	166	13	1720	1320	8.5
6.50-10	10	5.00F	590	186	15	1955	1500	7.75
7.00-12	14	5.00S	676	197	19	2750	2120	9
7.00-15	14	5.50F	762	203	19	3200	2450	9
7.50-15	14	6.00G	802	215	19	3650	2800	9.25
28x9-15	14	7	706	231	20	3775	2900	10
8.25-15	14	6.5	830	250	20	4000	3250	8
250-15	16	7.5	735	250	20	4380	3350	8.5
300-15	20	8	840	300	21	6340	4875	9.5

All dimensions are nominal and we reserve the right to make changes any time without notice

Notes:

1. Tantor Industrial Pneumatic tyres are strictly designed for Non-Highway use ONLY
2. Service life depends on severity of operating conditions
3. When fitting tyres for any particular wheel position of a vehicle or for application the specified and approved load and maximum design speed should always be observed
4. Tyre inflation pressures are specified (cold condition) and over-inflating or exceeding loads and speeds is not recommended
5. Always use approved rims and wheels and follow guidelines of ETRTO and US-TRA

Website: [www.sun-tws.com](http://www.sun-tws.com)

Contact: [crm@sun-tws](mailto:crm@sun-tws), [info@sun-tws.com](mailto:info@sun-tws.com)

Corporate Office:

**SUN TYRE & WHEEL SYSTEMS**  
 180 Mount Road, Chennai 600006, India  
 Phone #: +91-44-28525289

Manufacturing locations:

Plant #1 at A1-F3/A, New Sidco Industrial Estate  
 Maraimalainagar 603209, India

Plant #2 at Lot 2, Block B, Biyagama Export Processing Zone  
 Colombo, Sri Lanka

Plant # 3 Under Construction @  
 7/B1, Sipcot Industrial Complex, Pudukottai,  
 Tamil Nadu, India